

Pressure-sensitive adhesives

Acrylic

Film

WHITE BOPP DT / TR1 @ 1.0 Cwt. / 40#SCK L-3

ITEM #86103

Facestock

A white topcoated synthetic, thermal label facestock with exceptional smoothness. This lightweight product has high durability and exceptional yield, as well as environmental and water resistance.

	_		
Т	٠,	n	
	v	v	c

Film

Tensile MD Tensile CD

5.2 13.5

Elong MD Elong CD 220 38

Properties Value

Caliper 4.0 Mil

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
Yes
CPSIA
Yes
No

Adhesive

A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.

CompositionTypeShearAcrylicRemovable35

Application Temperature Min. Application Temperature Max. Application Temperature

40 F -65 F 120 F

PropertiesValueStainless Steel1.8 lbs/linear in.Glass0.0Polyethylene0.0

^{*}Please contact your sales representative for details

Corrugated 0.55 lbs./in.

Painted Metal 1.2 lbs/linear in.

Loop Tack 1.35 lbs./in.

Regulatory Approval

RoHSProp65REACHYesYesYes

TPCHCPSIAULYesYesNo

Direct Food Indirect Food

No Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type

5517342

Tensile MDTensile CD34 Lbs/In22 Lbs/In

Tear MDTear CD32 Grams34 Grams

Description	Value

Basis Weight 40 Lbs/Rm

Caliper 2.5 Mil

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
CPSIA
Yes
No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 222 Mound Avenue Miamisburg, OH 45342

orders.us@beontag.com

800-358-4448