

Pressure-sensitive adhesives

Acrylic

WHITE TT BOPP / TS523 @ 1.5 Cwt. / 50#SCK L-3

ITEM #8477

Facestock

A 2.6 Mil matte white polypropylene film that is designed for thermal transfer printability. Features good weather resistance and dimensional stability.

Type

Film

Tensile MD Tensile CD 13800 26800 **Elong MD Elong CD**

170 55

Properties Value

2.6 mil Caliper

Regulatory Approval

RoHS REACH Prop65 Yes Yes Yes **TPCH CPSIA FSC** Yes No Yes

Adhesive

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

Composition	Туре	Shear
Acrylic	Permanent	300
A !' !' T	Batter Accellentian Terror constants	NA

Application Temperature Min. Application Temperature Max. Application Temperature

35 F -65 F 180 F

Properties	Value
Stainless Steel	5.2 lbs/linear in.
Glass	2.8
Polyethylene	2.9

^{*}Please contact your sales representative for details

Corrugated 1.40 lbs./in.

Painted Metal 5.2 lbs/linear in.

Loop Tack 2.20 lbs./in2

Regulatory Approval

RoHSProp65REACHYesNoYes

TPCHCPSIAULYesYesNo

Direct Food Indirect Food

No Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type

5517353

Tensile MD

40 Lbs/ln

Tear MD

44 Grams

Tensile CD

24 Lbs/ln

Tear CD

48 Grams

Description Value

Basis Weight 50 Lbs/Rm

Caliper 3.2 Mil

Regulatory Approval

RoHS
YesProp65
YesREACH
YesTPCH
YesCPSIA
YesUL
No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 222 Mound Avenue Miamisburg, OH 45342

orders.us@beontag.com

800-358-4448