

Release Liner

## 2.0 MIL PET L-3 UV LINER

ITEM #19919

## Liner

A 2 mil polyester liner which has been silicone coated on one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end usage, making it an outstanding liner for high speed, automatic applications.

Туре

19919

Tensile MDTensile CD38500 PSI38500 PSI

Tear MD Tear CD Grams

**Description** Value

Caliper 2.0 Mil

## **Regulatory Approval**

RoHS
Yes
Yes
Yes

TPCH
Yes
Yes

CPSIA
Yes
No

## **Direct Food**

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

800-358-4448

orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details