

Release Liner

3.4 MIL LAYFLAT L-3

ITEM #517931

Liner

A bleached kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand die-cutting, marginal punching, perforating, fanfolding and refolding process while providing excellent dimensional stability.

| Tensile MD | Tensile CD | |
|---------------------|------------|-------|
| 35 | 15 | |
| Tear MD | Tear CD | |
| 50 | 75 | |
| Description | Value | |
| Basis Weight | 0 | |
| Caliper | 3,4 | |
| Regulatory Approval | | |
| RoHS | Prop65 | REACH |
| Yes | Yes | Yes |
| ТРСН | CPSIA | |
| Yes | Yes | |

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
222 Mound Avenue Miamisburg, OH 45342
800-358-4448

orders.us@beontag.com