



Release Liner

92# STA FLAT LINER L-10 UV

ITEM #17192

Liner

A bleached silicone coated poly kraft which has been polyethylene coated 2 sides (C2S) and silicone coated 1 side (C1S) to give a controlled release. It has superb smoothness, excellent dimensional stability and exceptional layflat characteristics.

Type

17192

Tensile MD

54 Lbs/In

Tensile CD

27 Lbs/In

Tear MD

110 Grams

Tear CD

120 Grams

Description

Value

Basis Weight

92 Lbs/Rm

Caliper

7.0 Mil

Regulatory Approval

RoHS

Yes

TPCH

Yes

Prop65

Yes

CPSIA

Yes

REACH

Yes

UL

No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com