

Linerless

Hot Melt

# Linerless Paper Standard 76g LLP 214

### **Facestock**

A white non-top-coated thermal paper, providing a black thermo-sensitive image with standard sensitivity. Good resistance to fat, oil, water and heat. The material is produced without any added Phenol. The paper has a siliconized surface.

This product offers a good performing, besides to be a sustainable solution for variable information.

#### Image color

Black

Properties	Method	Value
Basis Weight	ISO 536	76 ± 6g/m <sup>2</sup>
Caliper	ISO 534	71 ± 7µ

#### **Adhesive**

A general purpose permanent adhesive designed for cutters or cutting equipment to prevent residue on the knife or set off on the platen roller.

LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.

Туре	Composition	Min. Application Temperature
Permanent	Hot Melt	8°C

Min. Service Temperature Max. Service Temperature  $-10^{\circ}\text{C}$ 

Properties	Method	Value
Typical Loop Tack (Filmic Substrate)	FTM9	20 N/25mm

## **Regulatory Approval**

FDA 21 CFR 175.105, BfR XIV

No

## **Final product**

Description	Method	Value		
Typical Caliper	-	80 ± 5µ		
Typical Loop Tack (Filmic Substrate)	FTM9	20 N/25mm		
<b>Min. Application Temperature</b> 8°C	<b>Min. Service Temperature</b> -10°C	<b>Max. Service Temperature</b> 70°C		
<b>Format</b> Roll				
Material Shelf Life 12 months stored at 20°C/50% RH non UV/Sunlight				

Last update: 20/02/2024

- 1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
- 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
- 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS: LINERLESS AB Pål Anders Väg 6 SE-263 34 Höganäs – Sweden sales.linerless@beontag.com or info.linerless@beontag.com