

FSC ScandTag NTC 14XM



FACESTOCK

ScandTag NTC 14X MA is a white woodfree card, coated with thermosensitive coating (black imaging). - Designed for non-hostile environments and low risk conditions where there is no requirement for surface - protection against contaminants or scuffing. - ScandTag NTC 14X MA should be used only in relatively clean, dry environments for short term labelling - applications. - ScandTag NTC 14X MA can be printed using water based and UV inks, designed for use with direct thermal - label papers, but it is not varnishable. - This thermosensitive product is designed for thermal print speeds up to 200 mm/s, depending on printer set up. - It is recommended that customers assess both the pre-print and the overprint characteristics under end use - conditions before proceeding to long runs.

Type

Paper

Image color

Black

Printing speed (Max.)

200mm/s

PROPERTIES	METHOD	VALUE
Basis Weight	ISO 536	156 ± 15g/m²
Caliper	ISO 534	146 ± 15µ
Brightness	ISO 2470 (R457-)	> 80%
Smoothness	ISO 5627 (Bekk)	> 200s
Roughness	ISO 8791 (PPS) RS	3,4¼

REGULATORY APPROVAL

FSC

Yes

FINAL PRODUCT

Format

Roll

Certificate

The product is registered to SAI-COC-010567 FSC™ Mix credit.

Material Shelf Life

Min. 2 years, stored at 20°C/50% RH

SKU

FNTC14XM

Replaces all previous information.

and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com