

FSC ScandPrint T SSP 50N HG0



FACESTOCK

ScandPrint T is a smooth and matt, white pigmented woodfree printing paper with superior brightness, specially - designed for use in thermal transfer printers. - ScandPrint T has long lasting readability thanks to the high-definition printing performance and resistance to - scratch and smudge.

Type
Paper

| PROPERTIES | METHOD | VALUE |
|--------------|----------|------------------------|
| Basis Weight | - | 85 ± 3g/m ² |
| Caliper | ISO 534 | 77 ± 5µ |
| Opacity | ISO 2471 | 90% |

REGULATORY APPROVAL

FSC
Yes

ADHESIVE

ScandStick Permanent 50N has excellent initial tack with high bond strength at elevated, room and chilled temperatures, as well as in moist conditions. It has been formulated to adhere to a wide variety of substrates, including corrugated cardboard, low surface energy materials like polyethylene and non-polar surfaces. SSP 50N provides enhanced conversion characteristics, allowing die-cutting at higher speeds and is designed for both paper and synthetic face materials. Limitation: Not suitable for labelling plasticised PVC.

General purpose chill permanent

| | | |
|----------------------------------|--------------------------------------|-----------------------------------|
| Type Permanent | Min. Application Temperature -5°C | Min. Service Temperature -40°C |
| Max. Service Temperature 70°C | | |

| PROPERTIES | METHOD | VALUE |
|------------|----------------|-------|
| Peel | FTM 1 (20 min) | 19N |
| Tack | FTM 9 | 18N |

REGULATORY APPROVAL

| | | |
|--------------------|----------------------|--|
| Direct Food Yes | Indirect Food Yes | Food contact Meets composition requirement of indirect food additives regulation FDA175.105, BfR XIV. |
|--------------------|----------------------|--|

ISEGA approved for direct contact with
dry and moist non-fatty foods
Yes

BACKING

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type
Paper

| DESCRIPTION | METHOD | VALUE |
|--------------|----------|---------|
| Caliper | ISO 534 | 49 ± 3µ |
| Transparency | ISO 2469 | 50% |

FINAL PRODUCT

| DESCRIPTION | VALUE |
|-----------------|-----------|
| Typical Caliper | 134 ± 10µ |

Format
Roll

Certificate
The product is registered to SAI-COC-010567 FSC™ Mix credit.

Regulations
Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs. Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.

Material Shelf Life
12 months stored at 20°C/50% RH

SKU
F115000J0N000

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:
Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50
orders.scandstick@beontag.com