

ScandMet S SSP713 HG0

Description

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

Facestock

ScandMet S is a bright silver metallised printing paper, that has been coated with a print receptive acrylic lacquer. The material offers top print quality by all conventional print methods, like flexography, letterpress, offset and screen. Note that special inks for non-absorbent materials should be used.

Type

Paper

Properties	Method	Value
Basis Weight	ISO 536	74 ± 3g/m ²
Caliper	ISO 534	73 ± 5µ
Smoothness	ISO 5627	> 12900s

Backing

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type

Paper

Description	Method	Value
Caliper	ISO 534	49 ± 3µ
Transparency	ISO 2469	0.5

Final product

Description	Value
-------------	-------

Typical Caliper

142 ± 10μ

Format

Roll

Material Shelf Life

12 months stored at 20°C/50% RH

Last update: 01/05/2024

ADDRESS:

Beontag

Pål Anders väg 4, 263 35

Höganäs, Sweden

+46 42 25 00 50

orders.scandstick@beontag.com