

Self adhesives

Hot Melt

Paper

ScandMet S SSP713 HG0

Description

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

Facestock

ScandMet S is a bright silver metallised printing paper, that has been coated with a print receptive acrylic lacquer. The material offers top print quality by all conventional print methods, like flexography, letterpress, offset and screen. Note that special inks for non-absorbent materials should be used.

Type

Paper

Properties	Method	Value
Basis Weight	ISO 536	74 ± 3g/m ²
Caliper	ISO 534	73 ± 5µ
Smoothness	ISO 5627	> 12900s

Adhesive

SSP713 has excellent initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Particularly good adhesion to cardboard, plastic and glass. Note: Not advised for labelling highly plasticised materials, eg: flexible PVC

Composition Hot Melt	Type Permanent	Min. Application Temperature 8°C
Min. Service Temperature -10°C	Max. Service Temperature 70°C	

Typical Adhesion values

Properties	Value
Stainless Steel	18N

Regulatory Approval

Food contact Complies with FDA175.105, BfR XIV.	FDA 21 CFR 175.105, BfR XIV Yes	ISEGA approved for direct contact with dry and moist non-fatty foods
-----------------------------------------------------------	-------------------------------------------	-----------------------------------------------------------------------------

Yes

Backing

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type

Paper

Description	Method	Value
Caliper	ISO 534	49 ± 3μ
Transparency	ISO 2469	0.5

Final product

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

Format

Roll

Description	Value
Typical Caliper	142 ± 10μ

Regulatory Approval

Material Shelf Life

12 months stored at 20°C/50% RH

Last update:

ADDRESS:

Beontag

Pål Anders väg 4, 263 35

Höganäs, Sweden

+46 42 25 00 50

orders.scandstick@beontag.com