

Linerless

Papel

Linerless Paper Standard 76g LLP 214

Frontal

Tipo

Papel

Image color

Black

Properties	Método de prueba	Valor
Gramaje	ISO 536	76 ± 6g/m ²
Familia	ISO 534	71 ± 7μ

Adhesivo

LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.

Tipo

Permanente

Temperatura de Aplicación

8°C

Mínima Temperatura de Servicio

-10°C

Máxima Temperatura de Servicio

70°C

Properties	Método de prueba	Valor
Loop Tack	FTM9	20 N/25mm

Producto final

Description	Método de prueba	Valor
Espesor Total (μ)	-	80 ± 5μ
Loop Tack	FTM9	20 N/25mm

Formato

Roll

Material Shelf Life

12 months stored at 20°C/50% RH non UV/Sunlight

Revisión: 20/02/2024

1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

DIRECCIÓN:

Beontag

Avenida Presidente Kennedy, 2427 - Jardim Lar Parana

Campo Mourão - PR, Brasil

+55 (44) 3518-3500