

# Linerless paper High Quality 81g LLP 214

Frontal		
<b>Image color</b> Black	<b>Printing speed (Max.)</b> 200mm/s	
Propriedades	Método	Valor
<b>Gramatura</b>	ISO 536	81 ± 4g/m²
<b>Espessura</b>	ISO 534	78 ± 5µ
Regulatory Approval		
<b>BPA Free</b> Sim	<b>Top Coating</b> Sim	

Adesivo		
LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.		
<b>Composição</b> Hot Melt	<b>Composição</b> Rubber	<b>Categoria</b> Permanente
<b>Application Temperature</b> 8°C	<b>Min. Application Temperature</b> -10°C	<b>Max. Application Temperature</b> 70°C
Propriedades	Método	Valor
<b>Typical Loop Tack (Filmic Substrate)</b>	FTM9	18N/25mm

Produto final		
<b>Formato</b> Roll		
Descrição	Método	Valor

Typical Caliper	-	87 ± 3μ
Typical Loop Tack (Filmic Substrate)	FTM9	18N/25mm

Regulatory Approval

Material Shelf Life

Keep the material in the original packaging when not used in order to protect it from dust and contamination. 12 months stored at 20°C/50% RH non UV/Sunlight

Última atualização: 01/05/2024

1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ENDEREÇO:  
Beontag  
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana  
Campo Mourão - PR, Brasil  
+55 (44) 3518-3500