

Linerless

Hot Melt

Rubber

Linerless paper High Quality 81g LLP 214

Frontal

Image color

Black

Printing speed (Max.)

200mm/s

Propriedades

Método

Valor

Gramatura

ISO 536

81 ± 4g/m²

Espessura

ISO 534

78 ± 5μ

Regulatory Approval

BPA Free

Sim

Top Coating

Sim

Adesivo

LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.

Composição

Hot Melt

Composição

Rubber

Categoria

Permanente

Application Temperature

8°C

Min. Application Temperature

-10°C

Max. Application Temperature

70°C

Propriedades

Método

Valor

Typical Loop Tack (Filmic Substrate)

FTM9

18N/25mm

Produto final

Formato

Roll

Descrição

Método

Valor

Typical Caliper	-	87 ± 3μ
Typical Loop Tack (Filmic Substrate)	FTM9	18N/25mm

Regulatory Approval

Material Shelf Life

Keep the material in the original packaging when not used in order to protect it from dust and contamination. 12 months stored at 20°C/50% RH non UV/Sunlight

Última atualização:

1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ENDEREÇO:

Beontag
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana
Campo Mourão - PR, Brasil
+55 (44) 3518-3500