

Linerless paper Top Coat 72g LLP 214

Frontal		
Tipo Papel		
Image color Black		Printing speed (Max.) 250mm/s
Propriedades	Método	Valor
Gramatura	ISO 536	72 ± 6g/m²
Espessura	ISO 534	80 ± 8µ

Adesivo		
LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.		
Composição Hot Melt	Composição Rubber	Categoria Permanente
Application Temperature 8°C	Min. Application Temperature -10°C	Max. Application Temperature 70°C
Propriedades	Método	Valor
Typical Loop Tack (Filmic Substrate)	FTM9	20 N/25mm

Produto final		
Descrição	Método	Valor
Typical Caliper	-	89 ± 6µ
Typical Loop Tack (Filmic Substrate)	FTM9	20 N/25mm
Regulatory Approval		
Material Shelf Life		

12 months stored at 20°C/50% RH non UV/Sunlight

Última atualização: 20/02/2024

- 1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
- 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
- 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ENDEREÇO:
Beontag
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana
Campo Mourão - PR, Brasil
+55 (44) 3518-3500