

Linerless paper Top Coat 72g LLP 214

FRONTAL

Tipo
Papel

Image color
Black

Printing speed (Max.)
250mm/s

PROPRIEDADES	MÉTODO	VALOR
--------------	--------	-------

Gramatura (g/m²)	ISO 536	72 ± 6g/m ²
------------------------------------	---------	------------------------

Espessura (μ)	ISO 534	80 ± 8μ
----------------------	---------	---------

ADESIVO

Tipo
Permanente

Composição
Hot Melt

Composição
Rubber

Temperatura mínima de aplicação
8°C

Temperatura mínima de serviço
-10°C

Temperatura máxima de serviço
70°C

PROPRIEDADES	MÉTODO	VALOR
--------------	--------	-------

Loop Tack (kgf/pol)	FTM9	20 N/25mm
----------------------------	------	-----------

PRODUTO FINAL

PROPRIEDADES	MÉTODO	VALOR
--------------	--------	-------

Espessura total (μ)	-	89 ± 6μ
----------------------------	---	---------

Loop Tack (kgf/pol)	FTM9	20 N/25mm
----------------------------	------	-----------

Material Shelf Life

12 months stored at 20°C/50% RH non UV/Sunlight

Revisão: 20/02/2024

- All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
- Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
- This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ENDEREÇO:

Beontag
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana
Campo Mourão - PR, Brasil
+55 (44) 3518-3500